


FOOD WARMER





MODEL: FW18

PREPARED BY: _		
TYPE:		
0401100411111104		
DATE:		
CERTIFICATION:	UL Listed NSF Approved	
021111110711101111	• • • • • • • • • • • • • • • • • • • •	

FW18/58/BLC

Finish – Five stage pretreatment process, coated with a lead free TGI C polyester powder coat finish. White is standard inside reflectors. See color chart below for color options. Some finish options are not available for certain fixtures. Custom color options are available upon request.

Lamp – Food Warmer – medium base porcelain socket, copper shell with nickel plate, rated 250v, 660W. 250 Watt Infrared R40 Bulb, available in clear or red, shatter proof coated or non-coated.

Decorative Applications – Can accommodate LED, Compact Fluorescent, Incandescent, or High Intensity Discharge (H.I.D.). **Mounting** – Available with cord (BLC, WHC), cord and cable (TCB, TCW), retractable telephone cord and cable (PTB, PTW), non-retractable telephone cord and cable (TLB, TLW), flexible stem (FA), rigid stem (ST), or horizontal arm (AM). Supplied with ½" tapped hub with ST, AM, and FA. FA available in 12", 18", or 24". ST standard 12", available in custom lengths, minimum 6". AM standard 11", available in custom lengths, restrictions apply. ST finish will match fixture finish. Fixtures are pre-wired with 48" or 96" leads or 96" cord.

Accessories - Available with canopy mounted (TSC), fixture mounted (TSF), or remote switch (TSR). Available with track adapter (ADP) and track (HTR). HTR available in 4', 8' or 12', black or white.

REFLECTOR – Spun from heavy gauge 1100-0 aluminum, ranging in thickness from .050 to .125.

MODEL# F	FINIOU	LIGHT SOURCE		INTING OPTIONS	ACCESSORIES
	FINISH	INC	IVIO	MOUNTING OPTIONS	ACCESSORIES
FW18 ²	21P, 41, 42, 43, 44, 45, 48*, 49*, 50, 51, 52, 53, 57*, 58*, 59, 61*, 62*, 70*, 71*, 74, 75, 76, 79, 81, 84*, 87, 88*, 90, 93*, 95, 97	250WRU ¹	BLC, N TCB, T TLB, T PTB, F FA12, ST12 AM11 TP	CW LW	TSC TSF TSR HTRB-4 HTRW-4 HTRB-8 HTRW-8 HTRW-12 HTRW-12 ADP

^{*} same finish color inside and out. 1. not NSF approved. 2. not available with 375 watt bulb.

.SUBJECT TO MODIFICATION WITHOUT NOTICE.





