

ام جي كيه للاعمال الكهر وميكانيكية ش ذم م

## MGK ELECTROMECHANICAL WORKS L.L.C.

	Manufacturer Cool Compact
C 4 4	
C Stem	Model no. AKM021200 Solid Waste Refrigerator 2 x 120 L
Capilli	AKM021200 Solid Waste Refrigerator 2 x 120 L
	Product Description
	Solid waste refrigerator for two 120 liters waste bin, with foamed-in evaporator system
	in the stainless steel back wall, with hinged
	poor-in aperture, electronic control, equipment
	ready mounted.
	Origin
17-	Germany
	SPECIFICATIONS
	SPECIFICATIONS
Form	• Temperature: +2°C / +15°C
	<ul><li>Gross capacity: 750 liters</li><li>Refrigerant: R134a</li></ul>
	Built-in Cooling Automatic defrosting and evaporation of the defrost water
	using hot gas, refrigerating unit for ambient temperatures of up
	to 43°C, ready to plug in
	Dimensions: 1710 x 720 x 1060 mm (L x D x H) Height with open lid: 1450 mm
	Depth with open door: 1310 mm
	Connected load: 440 W / 230 V Refrigeration output: 380 W / -15°C evap. temp.
	Power consumption: 1,9 kWh / 24 h
Construction	Cool Compact Solid Waste Refrigerators appliances are basically made entirely of stainless steel (1.4301) inside and
	outside
	<ul> <li>no corrosion when properly cared for</li> </ul>
	easy to clean, long-lasting value
	Evaporator in stainless steel (1.4301) rear wall completely
	encased in insulating foam
	evaporator-free cooling compartment
	> no soiling and no bacteria in the evaporator fins

MGK ELECTROMECHANICAL WORKS LLC



## MGK ELECTROMECHANICAL WORKS L.L.C.

	<ul> <li>no corrosion or pitting due to aggressive goods         <ul> <li>unlimited unit lifetime, lower operating costs</li> <li>uniform temperature distribution throughout the storage compartment</li> <li>only smooth surfaces             <ul></ul></li></ul></li></ul>
Engineering / MEP Ratings	Power Consumption/ Self-Cooling: 440 W / 230 V
Capacity	2 waste bin 120 liters
Special Requirement	<b>Series AKM/AAKM:</b> Solid waste refrigerator with aggregate, built-in cooling system, ready to plug-in.